




Method and Apparatus for Processing Requests in a Network System based on a Trust Association Between Servers

1/5





400

FIG. 4A

com.ibm.websphere.security.trustassociation.enabled=true 402
 com.ibm.websphere.security.trustassociation.types=webseal36 404
 com.ibm.websphere.security.trustassociation.webseal36.interceptor=com.ibm.ejs.security.web.
 WebSealTrustAssociationInterceptor 406
 com.ibm.websphere.security.trustassociation.webseal36.config=webseal36a 408

410

FIG. 4B

webseal36a.properties: 412
 com.ibm.websphere.security.webseal36.id=iv-creds
 com.ibm.websphere.security.webseal36.hostnames=vivaldi.raleigh.ibm.com, vivaldi
 com.ibm.websphere.security.webseal36.ports=444

FIG. 5





FIG. 6



5/5

700

```
package com.ibm.websphere.security.web;
public interface TrustAssociationInterceptor
{
```

```
/**
```

Every interceptor should know which HTTP requests originate from the third party server that it is supposed to work with. Given an HTTP request, this method must be used to determine whether or not this interceptor is designed to process the request, in behalf of the trusted server it is designed to interoperate with. If the return value is false or an exception is thrown, then WebSphere will consider that the request is not routed via the trusted proxy server the interceptor is designed to handle. WebSphere will pass the request to the next interceptor till there is no more interceptors available, in which case it will be treated to be a directly submitted request.

```
**/
```

```
public boolean is TargetInterceptor(HttpServletRequest req)
throws WebTrustAssociationException;
```

```
/**
```

This method is used to determine whether the interceptor trusts the server through which the request has been routed. This may involve authenticating the server in some manner. All the required information to perform this operation should be available in the HTTP request.

If the third party server failed the validation, or is unable to provide the required information, a `WebTrustAssociationFailedException` must be thrown. This would be treated as an authentication failure and WebSphere would deny access to the requested secure resource.

```
**/
```

```
public void validateEstablishedTrust (HttpServletRequest req)
throws WebTrustAssociationFailedException;
```

```
/**
```

This method is used to retrieve the username of the end client (or the originator of the HTTP request). This method will be invoked if the `validateEstablishTrust` method invocation was successful.

The method returns a string. A return value of null or a `WebTrustAssociationUserException` should be thrown if the username is not available in the request header or the implementation determines that the username provided was invalid (based on some criteria, e.g., a list of valid usernames may have been decided earlier).

```
**/
```

```
public String getAuthenticatedUsername (HttpServletRequest req)
throws WebTrustAssociationUserException;
```

FIG. 7